



# Cabot® Wood Toned Deck & Siding Stain

## #3000 Series

### DESCRIPTION

**Cabot® Wood Toned Deck & Siding Stain** is specially formulated with a unique blend of resin and oil to provide a superior, natural finish for bare wood. Easy to apply, Cabot Wood Toned Stain slightly darkens wood when first applied, leaving a flat, translucent-toned finish, which weathers with time to a natural wood hue. For use on new or reconditioned exterior wood only, including decks, siding, fences and trim. Also suitable for use on shingles, shakes and log homes.

### PRODUCT FEATURES

- Water repellent
- Deep-penetrating oil
- Fade resistant
- A translucent oil stain that highlights wood's natural beauty

### FOR USE ON

New or reconditioned exterior wood only, including decks, siding, fences and trim. Also suitable for use on shingles and shakes.

### TINTING

Do not tint this product.

### COVERAGE

On smooth surfaces approximately 400–600 sq. ft. (37–55 m<sup>2</sup>) per gallon. On rough surfaces, 200–300 sq. ft. (19–28 m<sup>2</sup>) per gallon.

**Square feet can be calculated by multiplying length and width; e.g., 10' W x 25' L = 250 sq. ft. Requires a 1-coat application.**

### DRYING TIME

Approximately 24–48 hours depending on temperature and humidity.

### NOTE TO USER

The appearance of the finish will vary depending on the porosity and color of the wood surface. To ensure desired appearance and proper drying time, always finish a small test area before proceeding.

### SURFACE PREPARATION

Be sure surface is free of all dirt, mildew stains, loose wood fibers and other foreign matter. In order to be effective, a stain must be able to penetrate. Surfaces must be sound and absolutely dry. (Moisture content must be below 15% or wood must be exposed to dry weather a minimum of 3 to 5 days.)

Previously semi-transparent stained or weathered wood surfaces must be either sanded, scrubbed with a detergent solution or Cabot® Problem-Solver® Wood Cleaner and a stiff bristle brush, or power washed to remove the surface layer of all loose wood fibers, dirt, mildew stains, chalky residue and other foreign matter. Use Cabot® Problem-Solver® Strippers to safely remove oil stains and paints from wood surfaces. Use Cabot® Problem-Solver® Wood Brightener to easily remove nail and metal rust stains, and renew the wood's appearance. New smooth wood that is unseasoned or appears shiny should be allowed to weather sufficiently before staining.

**Extractive Bleeding:** Extractive bleeding is not caused by the coating, nor is it a coating failure. To remove discoloration caused by extractive bleeding, use Cabot® Problem-Solver® Wood Brightener. Follow directions on label.

**Mildew:** Any mildew stains present on the surface prior to application should be removed with Cabot® Problem-Solver® Wood Cleaner. Mildew stains are not caused by the coating, nor do they represent coating failure. This product contains agents that inhibit the growth of mildew on the coating's film.

### LEAD WARNING

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the USEPA/Lead Information Hotline at 1-800-424-LEAD (5323) or visit [www.epa.gov/lead](http://www.epa.gov/lead).

### APPLICATION

**Applicator:** Apply with a natural bristle brush or professional spray equipment. When spraying, always backbrush immediately. To ensure desired appearance and proper drying time, always finish a small test area before proceeding.

**Product application:** Do not overapply. Shake and stir thoroughly before and during use. If project requires more than 1 container, blend all containers together to ensure uniformity. Apply to small sections at a time (1–3 boards); start at one edge and follow through to the end of the boards to avoid lap marks. Apply 1 coat only. For wood substrates only.

**Airless Spray:** Recommended tip sizes and adjustments are 1000–1500 PSI, 0.013–0.015" tip with fan width of 8–10". These recommendations are a starting point only. Due to variability in sprayers, we recommend testing your spray pattern and flow before proceeding. If spraying large surfaces, be sure to back-brush or roll immediately after spraying. When using HVLP spray equipment, see manual for proper set-up instructions.

### RESTRICTIONS

Overapplication of this product may result in a glossy appearance, poor drying or sagging. Do not apply in direct sunlight, to hot surfaces, or when air or surface temperature is below 50 °F (10 °C) or may fall below 50 °F (10 °C) for 48 hours after application. Do not apply over wet or damp surfaces or when rain is imminent. **Do not intermix with any other products. Do not thin.** Do not apply over previously painted or sealed surfaces. **For exterior use only.**

### MAINTENANCE

UV rays (sunlight) and moisture (rain/snow/dew) are wood's natural enemies, so minimize exposure. Evaluate finish each spring and maintain as needed. Finish durability depends upon weather, wear and other local conditions, but finish typically lasts 1–2 years on decks and 1–3 years on siding and fences.



# Cabot® Wood Toned Deck & Siding Stain

## #3000 Series

### TECHNICAL DATA

**Pigment Type:** Trans-oxide/oxide pigments  
**Vehicle Type:** Refined natural linseed oil modified with alkyl resin  
**Solvent Type:** Aliphatic petroleum distillates  
**Viscosity:** 26–56 Units Centipoise  
**Flash Point:** over 100°F  
**V.O.C. Content:** < 550 g/L  
**Solids Weight:** 38%  
**Solids Volume:** 32%  
**Pigment Weight:** 1.4%  
**Density:** 7.2 lbs./gal.  
**Film Thickness:** Minimal because Cabot Wood Toned Stain penetrates deeply into wood.  
**Water Repellent:** Yes  
**Mildew Resistant:** Yes

\*Data reported is typical of the Neutral Base and will vary by color and batch.

### REGULATORY COMPLIANCE

Current as of: 12/17/2014

SCAQMD	No
CARB 2000 SCM	No
CARB 2007 SCM	No
OTC/LADCO	No
US National	Yes

### PACKAGING

4 ready mix colors available in quarts, gallon and five gallon.

### BASE AND FILL LEVELS

	(oz./gal.)
<b>Natural</b> (3000)	128
<b>Cedar</b> (3002)	128
<b>Heartwood</b> (3004)	128
<b>Pacific Redwood</b> (3005)	128

### CLEANUP AND DISPOSAL

Clean up with mineral spirits or VOC compliant brush cleaner. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

**DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed, water-filled metal container. Dispose of according to local regulations.**

### WARRANTY

If this product does not perform as stated on the label after you apply it according to label directions, Cabot will either replace this product or refund its purchase price, at its option. Cabot disclaims all other implied or expressed warranties. Cabot will not provide or pay for labor for removal or application of the product. This warranty excludes all incidental or consequential damages. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

### CAUTIONS

**DANGER!** Contains Petroleum Distillates and Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. **Use only with adequate ventilation.** Keep away from heat, sparks and flame. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with the eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** NOTICE: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.\* **If Inhaled:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Do not induce vomiting. Get medical attention immediately.\*

\* Call poison control center, hospital emergency room or physician immediately

CS 6.3 HQG

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:**  
**1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631  
800-US-STAIN  
cabotstain.com  
Revised: 12/17/14  
Version: 3000G