



## TECHNICAL DATA

### TUNG OIL FINISH #8099 CLEAR FINISH

#### DESCRIPTION

##### *Recommended Uses:*

**Cabot Tung Oil Finish** imparts a striking hand-rubbed beauty to both bare and stained wood surfaces. The deep-penetrating formula revitalizes aged and refinished interior wood, restoring its natural beauty. For long-lasting protection, simply wipe on this premium Tung Oil Finish. Hand rub additional coats onto the surface for increased sheen and durability. Use on any bare or stained interior wood surface, where a natural wood look is desired.

**Do not apply to floors.** Tung Oil is not recommended for woods already sealed with protective finish.

##### *Composition:*

Tung-phenolic varnish

##### *Finish:*

This product has a clear, amber-colored finish

##### *Tinting/Intermixing:*

Cabot Tung Oil Finish cannot be tinted or intermixed with any other Cabot product.

##### *Coverage/Thinning:*

One quart covers up to 50-100 sq. ft. (4.6-9.3 m<sup>2</sup>) depending upon wood porosity. Do not thin.

##### *Packaging/Containers:*

Available in quart containers.

##### *Restrictions:*

**DO NOT USE OVER PRODUCTS THAT CONTAIN STEARATES.**

Do not apply when air or surface temperature is below 50°F.

Do not apply over wet or damp surfaces.

Do not thin or add colorant to this product.

Do not apply this product adjacent to cement or stucco. Do not use on decks or siding.

**FOR INTERIOR USE ONLY.**

#### TECHNICAL DATA

##### *Environmental Impact:*

These products are in compliance with V.O.C. (Volatile Organic Compounds) requirements for Specialty Architectural Coatings under current regulations. Call Cabot's Technical Services & Support for additional information pertaining to current V.O.C. rulings.

**WARNING! VAPOR HARMFUL. COMBUSTIBLE LIQUID & VAPOR.**

**DANGER: CONTAINS PETROLEUM DISTILLATES. COMBUSTIBLE:**

**DO NOT SMOKE.** Keep away from sparks, open flame, and lit cigarettes. Turn off stoves, heaters, electric motors, pilot lights and other sources of ignition during use and until all vapors are gone. Prevent build up of vapors by opening all windows and doors for cross ventilation.

**Emergency Medical Telephone:  
1-888-345-5732**

*Cleanup and Disposal:* Clean brushes and equipment with mineral spirits. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter.

Dispose of empty cans or unused portion in accordance with local, state and federal regulations. Material Safety Data Sheets (MSDS) are available upon request.

**DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in a sealed, water-filled metal container and dispose of according to local regulations.**

##### *Physical and Chemical Data:*

*Drying Time:* Penetrates in 5-10 minutes and dries in 6-8 hrs.

*Weight:* 6.95+/- .05 pounds per gallon.

*Flash Point:* 106°F (41°C)

*Film Thickness:* None because Cabot Tung Oil Finish penetrates into the wood, leaving no film build.

*Shelf Life:* A minimum of five (5) years in closed original containers.

*% Solids (weight):* 28 - 28.2

*% Solids (volume):* 23.5 - 23.7

*% Pigment (weight):* 0

*Viscosity:* 10-30 cps.

*Pigment Type:* N/A

*Vehicle Type:* Tung-phenolic varnish

*Solvent Type:* Aliphatic and Terpene Hydrocarbons

*V.O.C. Content:* GPL Maximum of 600 grams/liter (5.0 pounds/gallon)

## TUNG OIL FINISH #8099 CLEAR FINISH

### APPLICATION

#### *Surface Preparation:*

Apply only to bare or newly stained woods. Remove any old finishes, wax, grease or polishes. If necessary, wood should be sanded smooth in the direction of the wood grain, ending with fine (#220) grit sandpaper. Remove all sanding dust. Allow wood that has been stained with an oil-based stain to dry at least 24 hours.

**WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the USEPA/Lead Information Hotline at 1-800-424-LEAD (5323) or visit [www.epa.gov/lead](http://www.epa.gov/lead).**

#### *Application:*

This finish will have a slight amber color, and should be tested in an inconspicuous area to determine final effect. Apply liberally with a lint-free cloth or natural bristle brush in the direction of the wood grain. Allow to penetrate 5-10 minutes. Wipe off any excess Tung Oil. Allow to dry 6-8 hours. Sand lightly with fine grit sandpaper or fine steel wool and remove all sanding dust. Apply a second coat as before.

**A minimum of two coats is recommended.** Additional coats may be applied after proper drying time, and will result in higher gloss and surface film thickness.

*Drying Time:* Dries to the touch in 4-6 hours. Wait 6-8 hours before sanding and recoating. Dry times are longer in high humidity or cool temperatures. Apply only when surface and air temperatures are between 50-90°F (10-32°C) during application and drying time.

*Number of Coats:* A minimum of two coats is recommended.

### AVAILABILITY

Cabot Wood Care Products are sold throughout the United States and Canada. For a list of Cabot dealer locations, please contact Cabot's Technical Services & Support at 1-800-US-STAIN.

### WARRANTY

If this product does not perform as stated on the label after you apply it according to label directions, Cabot will either replace this product or refund its purchase price, at its option. Cabot disclaims all other implied or expressed warranties. Cabot will not provide or pay for labor for removal or application of the product. This warranty excludes all incidental or consequential damages. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

### MAINTENANCE

Minimal because Cabot Teak Oil penetrates deep into the wood.

### TECHNICAL SERVICES

For additional technical information see your specialized Cabot dealer or call Cabot's Technical Services & Support toll-free at 1-800-US-STAIN (877-8246).

### FILING SYSTEMS

For complete model specifications and technical data on all Cabot products, visit the Cabot Home Page at: [cabotstain.com](http://cabotstain.com).



**Cabot®**  
Newburyport, MA 01950  
Tel.: 800-US-STAIN  
Fax: 1-800-998-3299  
[cabotstain.com](http://cabotstain.com)