



Cabot® Australian Timber Oil - Aerosol

#3400 Series

DESCRIPTION

Cabot® Australian Timber Oil® is a unique blend of oils, originally formulated to protect dense Australian tallowwood, cambara and merbau from extreme exposures. It is a proven translucent-oil treatment that is specially formulated for decks, siding, railings and outdoor furniture.

Now available in Aerosols, offering the same color, premium beauty and protection in a convenient and quick spray.

- Aerosols available in four popular Australian Timber Oil colors – Natural, Honey Teak, Mahogany Flame and Jarrah Brown
- Helps finish staining projects faster
- Great for small projects like - spindles, lattice & hard to reach spots.
- Fortified with three premium oils - penetrates even dense exotic hardwoods.
- Superior sun and moisture protection.

Containing a precise blend of superb-grade linseed oil for maximum penetration, long-oil alkyds for durability and pure tung oil for color depth and water repellency, it delivers three-way oil protection. In addition, complex translucent iron-oxide pigments are added to ensure a lasting UV-absorbing surface rich with color and dimension.

FOR USE ON

For use on exterior wood surfaces: New or reconditioned wood decks, lattice, spindles, outdoor furniture, steps, railings, fences, siding, mailboxes, planters and benches.

TINTING

Do not tint this product.

COVERAGE

On smooth surfaces, approximately 35 sq. ft. (37–55 m²) per 12oz can.

Square feet can be calculated by multiplying length and width; e.g., 10' W x 25' L = 250 sq. ft. Requires a 1-coat application.

DRYING TIME

Approximately 24–48 hours. To prevent clogging after use, turn can upside down and press spray head for 3 seconds.

SURFACE PREPARATION

Read the Lead Warning paragraph. Be sure surface is free of all dirt, mildew stains, loose wood fibers and other foreign matter. Surfaces must be sound and absolutely dry. Avoid spraying in windy conditions. (Moisture content must be below 15% or wood must be exposed to dry weather a minimum of 3 to 5 days.) Prepare previously stained or weathered surfaces with Cabot® Problem-Solver® Wood Cleaner, Wood Brightener or Wood Strippers. On untreated weathered surfaces, scrubbing with a stiff bristle brush or sanding may be required to completely remove all loose wood fibers.

For new and weathered wood surfaces, a light sanding with 80–100 grit sandpaper is recommended to open the pores for maximum penetration. Use Cabot® Problem-Solver® Wood Stripper #8004 to help remove oil-based finishes from wood surfaces.

Extractive Bleeding: Extractive bleeding is not caused by the coating, nor is it a coating failure. To remove discoloration caused by extractive bleeding, use Cabot® Problem-Solver® Wood Brightener. Follow directions on label.

Mildew: Any mildew stains present on the surface prior to application should be removed with Cabot® Problem-Solver® Wood Cleaner. Mildew stains are not caused by the coating, nor do they represent coating failure. This product contains agents that inhibit the growth of mildew on the coating's film.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the USEPA/Lead Information Hotline at 1-800-424-LEAD (5323) or visit www.epa.gov/lead.

APPLICATION

Danger: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed, water-filled metal container. Dispose in accordance with local, state and federal regulations.

Shake well for at least 1 minute, listening for rattle of mixing ball. Shake frequently during application. Hold can 8–10 inches from surface. Move can back and forth, releasing button after each stroke. Overlap each stroke. Apply 1 coat only. Do not over-apply. Brush in excess stain as needed.

Overspray: Cover nearby area to protect from spray mist.

RESTRICTIONS

Overapplication of this product may result in a glossy appearance, darker color, poor drying, and sagging. Do not apply in direct sunlight, to hot surfaces, or when air or surface temperature is below 50 °F (10 °C) or may fall below 50 °F (10 °C) for 48 hours after application. Do not apply over wet or damp surfaces or when rain is imminent. Do not apply over previously painted or sealed surfaces. **For exterior use only.**

MAINTENANCE

UV rays (sunlight) and moisture (rain/snow/dew) are wood's natural enemies, so minimize exposure. Evaluate finish each spring and maintain as needed. Finish durability depends upon weather, wear and other local conditions, but finish typically lasts 1–3 years on decks and 2–4 years on siding and fences.

NOTE TO USER

The appearance of the finish will vary depending on the porosity and color of the wood surface as well amount of stain sprayed onto the surface. To ensure desired appearance and proper drying time, always practice on a small test area before proceeding.



Cabot® Australian Timber Oil - Aerosol

#3400 Series

TECHNICAL DATA

Vehicle: Alkyd
Flash Point: -20°F
Weight/Gallon: 6.2186 lb/gal
VOC/MIR: MIR: WS 0.90/EPA 1.40
Coverage: 35 sq. ft.
Shelf Life: 24 months
Drying Time: Full Cure: 24-48 hours
Net Wt / Can Size: 12oz / 16oz

REGULATORY COMPLIANCE

Current as of: 5/22/2019

California	Yes
National Rule - EPA	Yes

PACKAGING

12oz can.

COLOR AND FILL LEVELS

	(oz.)
Natural (3400)	12
Honey Teak (3458)	12
Mahogany Flame (3459)	12
Jarrah Brown (3460)	12

CLEANUP AND DISPOSAL

Clean up with mineral spirits or VOC compliant brush cleaner. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed, water-filled metal container. Dispose of according to local regulations.

WARRANTY

If this product does not perform as stated on the label after you apply it according to label directions, Cabot will either replace this product or refund its purchase price, at its option. Cabot disclaims all other implied or expressed warranties. Cabot will not provide or pay for labor for removal or application of the product. This warranty excludes all incidental or consequential damages. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

CAUTIONS

CONTAINS ALIPHATIC HYDROCARBONS. DANGER! EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE — Extinguish all flames, pilot lights and heaters — Turn off stoves, electric tools and appliances, and any other sources of ignition. CONTENTS UNDER PRESSURE. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. VAPOR HARMFUL. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732

Cleveland, OH 44115
800-US-STAIN
cabotstain.com
Revised: 5/22/19
Version: 3400076