



Cabot® DeckCorrect

No. 25200

GENERAL DESCRIPTION

DeckCorrect™ by Cabot® covers and corrects worn, weathered, exterior wood and concrete. This thick coating is enhanced with Polycarbonate Everbeads™ to fill cracks up to 1/4" and lock down splinters for a durable, dirt-resistant surface.

PRODUCT FEATURES

- Use any standard 3/8" paint roller
- Fills cracks to 1/4"
- Locks down splinters
- Skid-resistant
- Hard finish resists dirt
- Hoses off easily
- Can be used on wood or concrete

WHERE TO USE

Recommended for use on properly prepared weathered wood and concrete surfaces such as decks, porches and steps

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material.

Packaging:

- Gallon — 4 per carton
- 5 gallon pail

COMPOSITION

Base and Fill Levels

(oz./gal.)

Tint Base

124

APPLICATION

Shake and stir thoroughly before and during use. If project requires more than 1 container, blend all containers together to ensure uniformity. Working in small sections at a time (1–3 boards), use a nylon/polyester brush to dab DeckCorrect™ into cracks and rough areas before rolling. Use a 3/8-inch nap roller to apply a thick, even coat, rolling lengthwise along boards. Allow to dry 4–6 hours before applying second coat. Requires a 2-coat application. For best results, on vertical surfaces such as railings, Cabot® Solid Color Stain is recommended.

Restrictions:

Do not apply in direct sunlight, to hot surfaces or when air or surface temperature is below 50 °F (10 °C) or may fall below 50 °F (10 °C) for 48 hours after application. Do not apply over wet or damp surfaces or when rain is imminent. Do not intermix with any other products. Do not thin. Protect containers from freezing. For exterior use only.

Extractive bleeding:

Extractive bleeding is not caused by the coating, or a coating failure. To remove discoloration caused by extractive bleeding, use Cabot® Wood Brightener.

CLEANUP AND DISPOSAL

Clean brushes and equipment with soap and water. Dispose of empty cans or unused portion in accordance with local, state and federal regulations.

PRODUCT SPECIFICATIONS

Vehicle Type: Acrylic

Gloss: 0–5 @ 60° angle

Flashpoint: 205 °F

VOC (g/L): less than 50 g/L

Volume Solids: 49–52%

Weight Solids: 63–65%

Weight Per Gallon: 11.26

Practical Coverage: Requires 2-coat application. One gallon covers approximately 75 sq. ft. with 2 coats.

Tinting: Neutral Base must be tinted with compatible universal colorants.

Recommended Film Thickness:

21 mil Wet 12 mil Dry

Dry Time: Approximately 4–6 hours, depending on temperature and humidity. Allow 24 hours before replacing furniture.

Application Temperature: 50–90 °F (10–32 °C)

Storage Temperature: 40–90 °F (5–32 °C)

Shelf Life: 2 years if unopened

Mildew resistance: yes

REGULATORY COMPLIANCE

Current as of: 1/16/2015

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.



Cabot® DeckCorrect

No. 25200

SURFACE PREPARATION

General:

Be sure surface is free of all dirt, mildew stains, loose wood fibers and other foreign matter. Surfaces must be sound and free of standing water. Remove loose splinters and replace severely damaged or rotting wood. Prepare previously stained or weathered surfaces with Cabot® Problem-Solver® Wood Cleaner, Wood Brightener or Wood Strippers. On severely weathered surfaces, sanding may be required to completely remove all loose wood fibers. Fill larger cracks with an exterior wood filler. Allow new concrete or masonry surfaces to cure for 30 days before coating with DeckCorrect™.

Mildew:

Any mildew stains present on the surface prior to application should be removed with Cabot® Problem-Solver® Wood Cleaner. Mildew stains are not caused by the coating, nor do they represent coating failure. This product contains agents that inhibit the growth of mildew on the coating's film.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

If this product does not perform as stated on the label after you apply it according to label directions, Cabot® will either replace this product or refund its purchase price, at its option. Cabot disclaims all other implied or express warranties. Cabot will not provide or pay for labor for removal or application of the product. This warranty excludes all incidental or consequential damages. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.*

*Call poison control center, hospital emergency room or physician immediately.

UCL 3.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

This product contains less than 50 g/L VOC

8725 W. Higgins Rd., Chicago, IL 60631
1-800-US-STAIN
cabotstain.com
Revised: 1/16/15
Version: 25200A