



TECHNICAL DATA

PRESERVATIVE WOOD FINISH

#4300 Series

DESCRIPTION

Recommended Uses:

Cabot Preservative Wood Finish penetrates deep into wood to provide long lasting protection. This Semi-Transparent stain is fortified with wood preservative to kill and resist mildew, mold and fungus growth. Durable and water repellent it is excellent for all exterior applications such as; decks, siding, fences, trim and especially rough-sawn siding. Recommended for exterior above grade application only.

Composition:

Lightly pigmented, deep penetrating, natural linseed oil-based stain.

Finish:

Dries to a natural, flat finish.

Colors:

Cabot Preservative Wood Finish is available in 4 ready-mixed colors. Additional colors may be achieved with the Cabot Preservative Wood Finish Neutral Base.

Tinting/Intermixing:

Cabot Preservative Wood Finish Neutral Base must be tinted with compatible universal colorants. Cabot Preservative Wood Finish may be intermixed within the Cabot Preservative Wood Finish Series to achieve color variations of the standard color palette.

Coverage:

On smooth surfaces, approximately 450-650 square feet per gallon; on rough surfaces, 200-300 square feet per gallon. These rates will vary depending upon the porosity of the surface.

Packaging/Containers:

Available in one-gallon and quart containers.

Restrictions:

Do not apply over previously painted or sealed surfaces, metal, masonry or adjacent to fresh stucco. Do not thin this product.

**Not intended for interior surfaces.
For exterior above grade use only.**

TECHNICAL DATA

GENERAL PRECAUTIONS AND RESTRICTIONS:

DO NOT apply this product in a way that will contact any person or pet.
DO NOT USE on interior surfaces.
DO NOT USE on wood used for food, feed or potable water contact.
DO NOT apply in direct sunlight or on days when air or surface temperatures are below 50°F (10°C).
DO NOT use where dairy and farm animals may come into contact with the treated wood.

Cover desirable plants and shrubs to avoid possible injury.

PRECAUTIONARY STATEMENTS:

WARNING: Causes skin irritation and moderate eye irritation. Do not get on skin or on clothing. Avoid contact with eyes. Wear protective clothing, chemical-resistant gloves and protective eyewear (goggles, face shield, or safety glasses) when handling. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing before reuse.

Cleanup and Disposal: Clean brushes and equipment with mineral spirits.

USER SAFETY RECOMMENDATIONS

Users should:

- Wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.
- Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.

FIRST AID

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

If on skin or clothing:

- Take off contaminated clothing.

- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

If swallowed:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told so by a poison control center or doctor.
- Do not give any liquid to the person.
- Do not give anything by mouth to an unconscious person.

In case of emergency call toll free 1-888-345-5732.

NOTE TO PHYSICIAN: Contains petroleum distillate. Vomiting may cause aspiration pneumonia.

Warning: This product contains chemicals known to the State of California to cause cancer.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply directly to water or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwater or rinsate.

PHYSICAL AND CHEMICAL HAZARDS: DO NOT USE, POUR SPILL OR STORE NEAR HEAT OR OPEN FLAME. PROTECT FROM FREEZING.

HAZARD NOTICE! --- SPONTANEOUS COMBUSTION: RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED, IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

PRESERVATIVE WOOD FINISH

#4300 Series

Pesticide Storage: Store product in original container within locked storage area.

Pesticide and Container Disposal:

Nonrefillable container. Do not reuse or refill this container.

If empty: Place in trash or offer for recycling if available.

If partly filled: Call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.

Physical and Chemical Data:

Water Repellent: Yes

Drying Time: Approximately 24-48 hours, depending on temperature and humidity.

Weight: 9.36 - 9.52 pounds per gallon.

Flash Point: Over 100°F TT-P-141 method 4293 closed cup.

Film Thickness: Minimal because Cabot Semi-Transparent Stains penetrate deeply into the wood.

Shelf Life: At least ten years in closed original containers at room temperature.

Mildew Resistant: Yes

% Solids (weight): 63 – 67.8

% Solids (volume): 56.3-60.7

Vehicle Type: Refined natural linseed oil/alkyd resin.

Solvent Type: Aliphatic petroleum distillates with a boiling range of 318-386°F (159-197°C).

V.O.C. Content: Maximum 350 grams/liter (2.9 lb/gal VOS)

APPLICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Apply this product only as specified on the label.

Surface Preparation:

Be sure surface is free of all dirt, mildew stains and loose wood fibers. Surfaces must be sound and absolutely dry (moisture content below 15%). Finish must be able to

penetrate wood surface. Prepare unpainted weathered wood with Cabot Problem-Solver® Wood Cleaner or Wood Brightener. Previously stained surfaces must be stripped with Cabot Wood Strippers.

Application of Coating:

Shake before and stir thoroughly during use. Inter-mix all containers of the same color.

Apply with a natural bristle brush or professional spray equipment. When spraying, always back-brush immediately to ensure uniformity. Start at one edge and follow through to a logical break. One coat is recommended.

Spray Application: Recommended tip sizes and adjustments for spray application are 0.013" - 0.015" at 1000-1500 PSI with a fan width of 8-10 inches; one gun. When using HVLP spray equipment, see manual for proper set-up instructions.

Number of Coats: **Only one coat is recommended.** Apply evenly and sparingly, or sagging and shiny areas (flashing) may develop.

Precautions:

Do not tint ready-mixed colors. Do not apply in direct sunlight, to hot surfaces, or when air or surface temperature is below 50°F or may fall below 50°F for 48 hours after application. Do not apply over wet or damp surfaces or when rain is imminent. Do not thin this product.

AVAILABILITY

Cabot Wood Care Products are sold throughout the United States and Canada. For a list of Cabot dealer locations, please contact Cabot's Technical Services & Support at 1-800-US-STAIN.

WARRANTY

If this product does not perform as stated on the label after you apply it according to label directions, Valspar will either replace this product or refund its purchase price, at its option. Valspar disclaims all other implied or express warranties. Valspar will not provide or pay for labor for removal or application of

the product. This warranty excludes all incidental or consequential damages. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

MAINTENANCE

Minimal because Cabot Preservative Wood Finish will not crack, peel or blister.

TECHNICAL SERVICES

For additional technical information, product line color cards, fan decks and liquid product samples, see your specialized Cabot Dealer or call the Cabot Wood Care Specialists in Technical Services & Support toll-free at 800-US-STAIN.

FILING SYSTEMS

For complete model specifications and technical data on all Cabot products, visit the Cabot Home Page at: cabotstain.com.



Cabot®

Newburyport, MA 01950

Tel.: 800-US-STAIN

Fax: 1-800-998-3299

cabotstain.com